

# LSW

A7

LED NON-CUTOFF WALL PACKS



### TECHNICAL SPECIFICATIONS:

- :: Back plate: Die-cast aluminum with mounting/gasket installed. Threaded 1/2" HUB provided
- :: Front: Polycarbonate lens and housing
- :: Includes pre-wired photo electric control, prewired to 120 volts
- :: 120~277V
- :: Non-cutoff optics ideal for maximum light distribution
- :: Vandal resistant housing ideal for exposed areas
- :: CRI: >80
- :: Power Factor: 95%
- :: Operating Temp:-4°F to 104°F
- :: 70,000 hour rated life
- :: 7-year warranty
- :: Suitable for Wet Locations, IP54

### APPLICATIONS:

- :: Ideal for general site lighting, loading docks, doorway, pathway and parking areas.



1/2" hub located on the back and bottom of housing for mounting versatility



## LED NON-CUTOFF WALL PACKS WITH PHOTOCELL

CATALOG NO.	WATTS	LUMENS	COLOR TEMP	REPLACEMENT RANGE	DIMENSIONS
LSW-22CW-PC	20W	2100LM	5000K	50~100 MH	11"(L) x 6-3/4"(W) x 5-1/8"(H)
LSW-22WW-PC	20W	2000LM	3500K	50~100 MH	
LSW-30CW-PC	30W	3000LM	5000K	100~125 MH	
LSW-30WW-PC	30W	2800LM	3500K	100~125 MH	

